

STANDARD BETAFENCE PANEL RANGE CHEAT SHEET

	Nylofor Medium	Betaview 25	Betaview 3	Betaview 3-4 Combo	Betaview 3D R	Securifor 3510 (full MTO)	Securifor 358	Securifor 2D	Securifor 358 Dublo	Securifor 358 Doubleskin
Wire diameter (mm) H & V	3,65 & 3,65	3 & 4	3 & 3*	3 & 4	3 & 3	3 & 3	4 & 4	4 & 5,65	4 & 4	4 & 4
Aperture (mm)	100 x 50	76 x 25	76 x 12	76 x 12	76 x 12	76 x 12	76 x 12	76 x 12	76 x 12	12 x 12
Panel Width (centre-centre between posts)	2515 mm	3070	3070	3070	3070	3000	3000	3365	3000	3000
Nominal Standard Heights** (m)	1,2 1,8 2	1,8 2,1 2,4	1,8 2,1 2,4	1,8 2,1 2,4	2,4	2 2,5 3,1	2,4 3	2,4	2,4 3	2,4 3
Post Heights** (m)	1,6 2,4 2,7	2,4 2,7 3	2,4 2,7 3	2,4 2,7 3	3	2,6 3,1 3,7	3 3,6	3	3 3,6	3 3,6
Profile	Bent	Bent Top rail optional	Bent Top rail optional	Bent Top rail optional	Bent Top rail optional	Flat Top rail as standard	Flat Top rail as standard	Flat Top rail as standard	Flat Top rail as standard	Flat Top rail as standard
Additional feature					Reinforcing strips welded on, at intervals.			Reinforcing horizontal wire welded to the reverse of the panel every 150mm.	Reinforcing vertical wire welded onto the reverse of the panel.	Two Securifor 358 panels welded together.

*4 & 4 available on request - Betaview 4

**Other heights available on request – MTO

Securing What Matters

COMMERCIAL IN CONFIDENCE
021 868 7300
011 314 8034

All Betafence companies and product names are trademarks owned by PRÆSIDIAD Group Limited.
Modification in products and assortment are subject to change without prior notice.